

AUTOTROL 255 ASSEMBLED SOFTENERS

REVISED 01.01.2010

255 RISER TWO TANK & CABINET SOFTENER SYSTEMS

| MODEL NUMBER | TANK SIZE | GRAINS CAPACITY | CUBIC FEET | BW Assy# | DLFC (Gpm) | INJECTOR COLOR | CLOCK LIST | METER LIST |
|---------------------------------|-----------|-----------------|------------|----------|------------|----------------|------------|------------|
| 255*R16 | 7x44" | 16,000 | .50cf | 7 | 1.3 | White-A | 611.14 | 793.80 |
| 255*R24 | 8x44" | 24,000 | .75cf | 8 | 1.7 | Blue-B | 632.84 | 815.50 |
| 255*R32 | 9x48" | 32,000 | 1.0cf | 9 | 2.2 | Blue-B | 676.26 | 858.93 |
| 255*R40 | 10x44" | 40,000 | 1.25cf | 10 | 2.7 | Blue-B | 706.35 | 889.02 |
| 255*R48 | 10x54" | 48,000 | 1.50cf | 10 | 2.7 | Blue-B | 742.17 | 924.84 |
| 255*R56 | 12x48" | 56,000 | 1.75cf | 12 | 3.9 | Red-C | 807.19 | 989.86 |
| 255*R64 | 12x52" | 64,000 | 2.0cf | 12 | 3.9 | Red-C | 841.74 | 1024.40 |
| 255*R80 | 13x54" | 80,000 | 2.50cf | 13 | 4.5 | Red-C | 928.18 | 1110.85 |
| CABINET SOFTENER SYSTEMS | | | | | | | | |
| 255*R16C | 7x35" | 16,000 | .50cf | 7 | 1.3 | White-A | 657.74 | 840.41 |
| 255*R24C | 9x35" | 24,000 | .75cf | 9 | 2.2 | Blue-B | 694.56 | 877.23 |
| 255*R32C | 10x35" | 32,000 | 1.0cf | 10 | 2.7 | Blue-B | 723.74 | 906.41 |

255 TURBULATOR TWO TANK & CABINET SOFTENER SYSTEMS

| MODEL NUMBER | TANK SIZE | GRAINS CAPACITY | CUBIC FEET | BW Assy# | DLFC (Gpm) | INJECTOR COLOR | CLOCK LIST | METER LIST |
|---------------------------------|-----------|-----------------|------------|----------|------------|----------------|------------|------------|
| 255*T16 | 7x35" | 16,000 | .50cf | 9 | 2.2 | White-A | 633.08 | 815.74 |
| 255*T24 | 7x44" | 24,000 | .75cf | 9 | 2.2 | Blue-B | 662.35 | 845.02 |
| 255*T32 | 8x44" | 32,000 | 1.0cf | 10 | 2.7 | Blue-B | 684.05 | 866.71 |
| 255*T40 | 9x48" | 40,000 | 1.25cf | 10 | 2.7 | Blue-B | 727.47 | 910.14 |
| 255*T48 | 10x44" | 48,000 | 1.50cf | 12 | 3.9 | Blue-B | 759.44 | 942.11 |
| 255*T56 | 10x47" | 56,000 | 1.75cf | 12 | 3.9 | Blue-B | 783.71 | 966.38 |
| 255*T64 | 10x54" | 64,000 | 2.0cf | 12 | 3.9 | Blue-B | 814.74 | 997.41 |
| 255*T80 | 12x48" | 80,000 | 2.50cf | 13 | 4.5 | Red-C | 903.99 | 1086.65 |
| CABINET SOFTENER SYSTEMS | | | | | | | | |
| 255*T16C | 7x35" | 16,000 | .50cf | 9 | 2.2 | White-A | 687.59 | 970.26 |
| 255*T24C | 8x35" | 24,000 | .75cf | 10 | 2.7 | Blue-B | 712.74 | 895.41 |
| 255*T32C | 9x35" | 32,000 | 1.0cf | 10 | 2.7 | Blue-B | 745.77 | 928.44 |
| 255*T40C | 10X35" | 40,000 | 1.25cf | 12 | 3.9 | Blue-B | 774.96 | 957.62 |

* ADD THE LETTER "M" TO THE MODEL NUMBER HERE IF UNIT IS METERED

STANDARD FEATURES

- POLYGLASS WOUND PRESSURE VESSEL
- HIGH CAPACITY CATION RESIN
- 1.050" DISTRIBUTOR SYSTEM
- 3/4 BRASS YOKE (FPT)
- 15X17" BRINE TANK (275LB SALT CAP)
- BRINE WELL WITH CAPS
- TYPE 6 BPU ASSEMBLY (BRINE PICK-UP)
- OVERFLOW FITTING
- OWNERS MANUAL
- SHIPPING CARTON

255-440i/460i CONTROL FEATURES

- CHOICE OF 6 OR 7 DAY CLOCK, OR METERED DEMAND
- 12VOLT TRANSFORMER PROVIDES SAFE INSTALLATION
- 5- CYCLE DOWNFLOW BRINING CONTROL VALVE
- 7 DAY VARIABLE RESERVE/CALENDAR OVERRIDE (460I ONLY)
- NON-CORROSIVE NORYL CONSTRUCTION
- AUTOTROL'S DESIGN MAKES DISASSEMBLY A SNAP
- CUSTOMIZE INSTALLATION CHOOSING FROM A WIDE RANGE OF OPTIONS (SEE PAGE 16)
- FLOW RATE IS UP TO 15GPM
- BACKWASH CAPACITY HANDLES TANKS UP TO 13" DIA.

For More Information On The Series 440i & 460i Control Valves
Please Call 800.426.9375 Or Visit www.pentairwater.com

SEE PAGE 16 FOR ACCESSORIES, DESIGNER TANK JACKETS AND OPTIONS

ALL PRICES F.O.B. SHIPPING POINT - TERMS NET (THIRTY) 30 DAYS

TOLL FREE ORDERING 800.426.9375
11470 Kreutzer Road - Huntley, Illinois 60142 - Office (847)669.1902 - Fax (847)669.1937

INTERNATIONAL WATERWORKS inc.
 E-Mail us @ iwaterwerks@aol.com
 Please visit our web site @ www.iwaterwerks.com
 PRICES SUBJECT TO CHANGE WITHOUT NOTICE

AUTOTROL L255 ASSEMBLED SOFTENERS

REVISED 01.01.2010

L255 RISER TWO TANK & CABINET SOFTENER SYSTEMS

| MODEL NUMBER | TANK SIZE | GRAINS CAPACITY | CUBIC FEET | BW Assy# | DLFC (Gpm) | INJECTOR COLOR | CLOCK LIST | METER LIST |
|---------------------------------|-----------|-----------------|------------|----------|------------|----------------|------------|------------|
| L255*R16 | 7x44" | 16,000 | .50cf | 7 | 1.3 | Peach-F | 603.84 | 746.77 |
| L255*R24 | 8x44" | 24,000 | .75cf | 8 | 1.7 | Tan-G | 625.53 | 768.47 |
| L255*R32 | 9x48" | 32,000 | 1.0cf | 9 | 2.2 | Lt.Purple-H | 668.96 | 811.90 |
| L255*R40 | 10x44" | 40,000 | 1.25cf | 10 | 2.7 | Lt.Blue-J | 699.05 | 841.99 |
| L255*R48 | 10x54" | 48,000 | 1.50cf | 10 | 2.7 | Lt.Blue-J | 734.87 | 877.80 |
| L255*R56 | 12x48" | 56,000 | 1.75cf | 12 | 3.9 | Pink-K | 799.89 | 942.83 |
| L255*R64 | 12x52" | 64,000 | 2.0cf | 12 | 3.9 | Pink-K | 834.43 | 977.37 |
| L255*R80 | 13x54" | 80,000 | 2.50cf | 13 | 4.5 | Orange-L | 920.88 | 1063.82 |
| CABINET SOFTENER SYSTEMS | | | | | | | | |
| L255*R16C | 7x35" | 16,000 | .50cf | 7 | 1.3 | Peach-F | 626.56 | 769.50 |
| L255*R24C | 9x35" | 24,000 | .75cf | 9 | 2.2 | Lt.Purple-H | 663.38 | 806.32 |
| L255*R32C | 10x35" | 32,000 | 1.0cf | 10 | 2.7 | Lt.Blue-J | 692.56 | 835.50 |

L255 TURBULATOR TWO TANK & CABINET SOFTENER SYSTEMS

| MODEL NUMBER | TANK SIZE | GRAINS CAPACITY | CUBIC FEET | BW Assy# | DLFC (Gpm) | INJECTOR COLOR | CLOCK LIST | METER LIST |
|---------------------------------|-----------|-----------------|------------|----------|------------|----------------|------------|------------|
| L255*T16 | 7x35" | 16,000 | .50cf | 9 | 2.2 | Peach-F | 625.77 | 768.71 |
| L255*T24 | 7x44" | 24,000 | .75cf | 9 | 2.2 | Peach-F | 655.05 | 797.99 |
| L255*T32 | 8x44" | 32,000 | 1.0cf | 10 | 2.7 | Tan-G | 676.74 | 819.68 |
| L255*T40 | 9x48" | 40,000 | 1.25cf | 10 | 2.7 | Lt.Purple-H | 720.17 | 863.11 |
| L255*T48 | 10x44" | 48,000 | 1.50cf | 12 | 3.9 | Lt.Blue-J | 752.14 | 895.08 |
| L255*T56 | 10x47" | 56,000 | 1.75cf | 12 | 3.9 | Lt.Blue-J | 776.41 | 919.35 |
| L255*T64 | 10x54" | 64,000 | 2.0cf | 12 | 3.9 | Lt.Blue-J | 807.44 | 950.38 |
| L255*T80 | 12x48" | 80,000 | 2.50cf | 13 | 4.5 | Pink-K | 896.68 | 1039.62 |
| CABINET SOFTENER SYSTEMS | | | | | | | | |
| L255*T16C | 7x35" | 16,000 | .50cf | 9 | 2.2 | Peach-F | 656.41 | 799.35 |
| L255*T24C | 8x35" | 24,000 | .75cf | 10 | 2.7 | Tan-G | 681.56 | 824.50 |
| L255*T32C | 9x35" | 32,000 | 1.0cf | 10 | 2.7 | Lt.Purple-H | 714.59 | 857.53 |
| L255*T40C | 10X35" | 40,000 | 1.25cf | 12 | 3.9 | Lt.Blue-J | 743.77 | 886.71 |

* ADD THE LETTER "M" TO THE MODEL NUMBER HERE IF UNIT IS METERED

STANDARD FEATURES

- POLYGLASS WOUND PRESSURE VESSEL
- HIGH CAPACITY CATION RESIN
- 1.050" DISTRIBUTOR SYSTEM
- 3/4 BRASS YOKE (FPT)
- 15x17" BRINE TANK (275LB SALT CAP)
- BRINE WELL WITH CAPS
- TYPE 6 BPU ASSEMBLY (BRINE PICK-UP)
- OVERFLOW FITTING
- OWNERS MANUAL
- SHIPPING CARTON

L255-740/760 CONTROL FEATURES

- SIMPLE ELECTRONIC 740 TIME CLOCK & 760 METER DEMAND
- 12VOLT TRANSFORMER PROVIDES SAFE INSTALLATION
- 28 DAY VARIABLE RESERVE (LOGIX 760 ONLY)
- HIGH EFFICIENCY REGENERATION SEQUENCE
- DOWNFLOW BRINING CONTROL VALVE
- NON-CORROSIVE NORYL CONSTRUCTION
- AUTOTROL'S DESIGN MAKES DISASSEMBLY A SNAP
- CUSTOMIZE INSTALLATION CHOOSING FROM A WIDE RANGE OF OPTIONS (SEE PAGE 16)
- FLOW RATE IS UP TO 15GPM
- BACKWASH CAPACITY HANDLES TANKS UP TO 13" DIA.

For More Information On The LOGIX 740 & 760 Control Valves
Please Call 800.426.9375 Or Visit www.pentairwater.com

SEE PAGE 16 FOR ACCESSORIES, DESIGNER TANK JACKETS AND OPTIONS

ALL PRICES F.O.B. SHIPPING POINT - TERMS NET (THIRTY) 30 DAYS

TOLL FREE ORDERING 800.426.9375
11470 Kreutzer Road - Huntley, Illinois 60142 - Office (847)669.1902 - Fax (847)669.1937

INTERNATIONAL WATERWORKS inc.
 E-Mail us @ iwaterworks@aol.com
 Please visit our web site @ www.iwaterworks.com
 PRICES SUBJECT TO CHANGE WITHOUT NOTICE

AUTOTROL LL255 ASSEMBLED SOFTENERS

REVISED 01.01.2010

LL255 RISER TWO TANK & CABINET SOFTENER SYSTEMS

| MODEL NUMBER | TANK SIZE | GRAINS CAPACITY | CUBIC FEET | BW Assy# | DLFC (Gpm) | INJECTOR COLOR | CLOCK LIST | METER LIST |
|---------------------------------|-----------|-----------------|------------|----------|------------|----------------|------------|------------|
| LL255*R16 | 7x44" | 16,000 | .50cf | 7 | 1.3 | Peach-F | 635.87 | 779.96 |
| LL255*R24 | 8x44" | 24,000 | .75cf | 8 | 1.7 | Tan-G | 657.56 | 801.65 |
| LL255*R32 | 9x48" | 32,000 | 1.0cf | 9 | 2.2 | Lt.Purple-H | 700.99 | 845.08 |
| LL255*R40 | 10x44" | 40,000 | 1.25cf | 10 | 2.7 | Lt.Blue-J | 731.08 | 875.17 |
| LL255*R48 | 10x54" | 48,000 | 1.50cf | 10 | 2.7 | Lt.Blue-J | 766.90 | 910.99 |
| LL255*R56 | 12x48" | 56,000 | 1.75cf | 12 | 3.9 | Pink-K | 831.92 | 976.01 |
| LL255*R64 | 12x52" | 64,000 | 2.0cf | 12 | 3.9 | Pink-K | 866.46 | 1010.55 |
| LL255*R80 | 13x54" | 80,000 | 2.50cf | 13 | 4.5 | Orange-L | 952.91 | 1097.00 |
| CABINET SOFTENER SYSTEMS | | | | | | | | |
| LL255*R16C | 7x35" | 16,000 | .50cf | 7 | 1.3 | Peach-F | 658.59 | 802.68 |
| LL255*R24C | 9x35" | 24,000 | .75cf | 9 | 2.2 | Lt.Purple-H | 695.41 | 839.50 |
| LL255*R32C | 10x35" | 32,000 | 1.0cf | 10 | 2.7 | Lt.Blue-J | 724.59 | 86/8.68 |

LL255 TURBULATOR TWO TANK & CABINET SOFTENER SYSTEMS

| MODEL NUMBER | TANK SIZE | GRAINS CAPACITY | CUBIC FEET | BW Assy# | DLFC (Gpm) | INJECTOR COLOR | CLOCK LIST | METER LIST |
|---------------------------------|-----------|-----------------|------------|----------|------------|----------------|------------|------------|
| LL255*T16 | 7x35" | 16,000 | .50cf | 9 | 2.2 | Peach-F | 657.80 | 801.90 |
| LL255*T24 | 7x44" | 24,000 | .75cf | 9 | 2.2 | Peach-F | 687.08 | 831.17 |
| LL255*T32 | 8x44" | 32,000 | 1.0cf | 10 | 2.7 | Tan-G | 708.77 | 852.87 |
| LL255*T40 | 9x48" | 40,000 | 1.25cf | 10 | 2.7 | Lt.Purple-H | 752.20 | 896.29 |
| LL255*T48 | 10x44" | 48,000 | 1.50cf | 12 | 3.9 | Lt.Blue-J | 784.17 | 928.26 |
| LL255*T56 | 10x47" | 56,000 | 1.75cf | 12 | 3.9 | Lt.Blue-J | 808.44 | 952.53 |
| LL255*T64 | 10x54" | 64,000 | 2.0cf | 12 | 3.9 | Lt.Blue-J | 839.47 | 983.56 |
| LL255*T80 | 12x48" | 80,000 | 2.50cf | 13 | 4.5 | Pink-K | 928.71 | 1072.80 |
| CABINET SOFTENER SYSTEMS | | | | | | | | |
| LL255*T16C | 7x35" | 16,000 | .50cf | 9 | 2.2 | Peach-F | 688.44 | 832.53 |
| LL255*T24C | 8x35" | 24,000 | .75cf | 10 | 2.7 | Tan-G | 713.59 | 857.68 |
| LL255*T32C | 9x35" | 32,000 | 1.0cf | 10 | 2.7 | Lt.Purple-H | 746.62 | 890.71 |
| LL255*T40C | 10X35" | 40,000 | 1.25cf | 12 | 3.9 | Lt.Blue-J | 775.80 | 919.90 |

* ADD THE LETTER "M" TO THE MODEL NUMBER HERE IF UNIT IS METERED

STANDARD FEATURES

- POLYGLASS WOUND PRESSURE VESSEL
- HIGH CAPACITY CATION RESIN
- 1.050" DISTRIBUTOR SYSTEM
- 3/4 BRASS YOKE (FPT)
- 15x17" BRINE TANK (275LB SALT CAP)
- BRINE WELL WITH CAPS
- TYPE 6 BPU ASSEMBLY (BRINE PICK-UP)
- OVERFLOW FITTING
- OWNERS MANUAL
- SHIPPING CARTON

LL255-742/762 CONTROL FEATURES

- SIMPLE ELECTRONIC 742 TIME CLOCK & 762 METER DEMAND
- FULLY PROGRAMMABLE CYCLE TIMES
- 12VOLT TRANSFORMER PROVIDES SAFE INSTALLATION
- 28 DAY VARIABLE RESERVE (LOGIX 762 ONLY)
- DOWNFLOW BRINING CONTROL VALVE
- NON-CORROSIVE NORYL CONSTRUCTION
- AUTOTROL'S DESIGN MAKES DISASSEMBLY A SNAP
- CUSTOMIZE INSTALLATION CHOOSING FROM A WIDE RANGE OF OPTIONS (SEE PAGE 16)
- FLOW RATE IS UP TO 15GPM
- BACKWASH CAPACITY HANDLES TANKS UP TO 13" DIA.

For More Information On The LOGIX 742 & 762 Control Valves
Please Call 800.426.9375 Or Visit www.pentairwater.com

SEE PAGE 16 FOR ACCESSORIES, DESIGNER TANK JACKETS AND OPTIONS

ALL PRICES F.O.B. SHIPPING POINT - TERMS NET (THIRTY) 30 DAYS

TOLL FREE ORDERING 800.426.9375

11470 Kreutzer Road - Huntley, Illinois 60142 - Office (847)669.1902 - Fax (847)669.1937

INTERNATIONAL WATERWORKS inc.
 E-Mail us @ iwaterworks@aol.com
 Please visit our web site @ www.iwaterworks.com
 PRICES SUBJECT TO CHANGE WITHOUT NOTICE

268 RISER TWO TANK & CABINET SOFTENER SYSTEMS

| MODEL NUMBER | TANK SIZE | GRAINS CAPACITY | CUBIC FEET | BW Assy# | DLFC (Gpm) | INJECTOR COLOR | CLOCK LIST | METER LIST |
|---------------------------------|-----------|-----------------|------------|----------|------------|----------------|------------|------------|
| 268*R16 | 7x44" | 16,000 | .50cf | 7 | 1.3 | White-A | 627.74 | 834.87 |
| 268*R24 | 8x44" | 24,000 | .75cf | 8 | 1.7 | Blue-B | 649.44 | 856.56 |
| 268*R32 | 9x48" | 32,000 | 1.0cf | 9 | 2.2 | Blue-B | 692.87 | 899.99 |
| 268*R40 | 10x44" | 40,000 | 1.25cf | 10 | 2.7 | Blue-B | 722.96 | 930.08 |
| 268*R48 | 10x54" | 48,000 | 1.50cf | 10 | 2.7 | Blue-B | 758.77 | 965.90 |
| 268*R56 | 12x48" | 56,000 | 1.75cf | 12 | 3.9 | Red-C | 823.80 | 1030.92 |
| 268*R64 | 12x52" | 64,000 | 2.0cf | 12 | 3.9 | Red-C | 858.34 | 1065.46 |
| 268*R80 | 13x54" | 80,000 | 2.50cf | 13 | 4.5 | Red-C | 944.73 | 1151.85 |
| CABINET SOFTENER SYSTEMS | | | | | | | | |
| 268*R16C | 7x35" | 16,000 | .50cf | 7 | 1.3 | White-A | 674.29 | 881.41 |
| 268*R24C | 9x35" | 24,000 | .75cf | 9 | 2.2 | Blue-B | 711.11 | 918.23 |
| 268*R32C | 10x35" | 32,000 | 1.0cf | 10 | 2.7 | Blue-B | 740.29 | 947.41 |

268 TURBULATOR TWO TANK & CABINET SOFTENER SYSTEMS

| MODEL NUMBER | TANK SIZE | GRAINS CAPACITY | CUBIC FEET | BW Assy# | DLFC (Gpm) | INJECTOR COLOR | CLOCK LIST | METER LIST |
|---------------------------------|-----------|-----------------|------------|----------|------------|----------------|------------|------------|
| 268*T16 | 7x35" | 16,000 | .50cf | 9 | 2.2 | White-A | 649.68 | 856.80 |
| 268*T24 | 7x44" | 24,000 | .75cf | 9 | 2.2 | Blue-B | 678.96 | 886.08 |
| 268*T32 | 8x44" | 32,000 | 1.0cf | 10 | 2.7 | Blue-B | 700.65 | 907.77 |
| 268*T40 | 9x48" | 40,000 | 1.25cf | 10 | 2.7 | Blue-B | 744.08 | 951.20 |
| 268*T48 | 10x44" | 48,000 | 1.50cf | 12 | 3.9 | Blue-B | 776.05 | 983.17 |
| 268*T56 | 10x47" | 56,000 | 1.75cf | 12 | 3.9 | Blue-B | 800.32 | 1007.44 |
| 268*T64 | 10x54" | 64,000 | 2.0cf | 12 | 3.9 | Blue-B | 831.35 | 1038.47 |
| 268*T80 | 12x48" | 80,000 | 2.50cf | 13 | 4.5 | Red-C | 920.53 | 1127.65 |
| CABINET SOFTENER SYSTEMS | | | | | | | | |
| 268*T16C | 7x35" | 16,000 | .50cf | 9 | 2.2 | White-A | 704.14 | 911.26 |
| 268*T24C | 8x35" | 24,000 | .75cf | 10 | 2.7 | Blue-B | 729.29 | 936.41 |
| 268*T32C | 9x35" | 32,000 | 1.0cf | 10 | 2.7 | Blue-B | 762.32 | 969.44 |
| 268*T40C | 10X35" | 40,000 | 1.25cf | 12 | 3.9 | Blue-B | 791.50 | 998.62 |

* ADD THE LETTER "M" TO THE MODEL NUMBER HERE IF UNIT IS METERED

STANDARD FEATURES

- POLYGLASS WOUND PRESSURE VESSEL
- HIGH CAPACITY CATION RESIN
- 1.050" DISTRIBUTOR SYSTEM
- 3/4 COPPER TAIL KIT (MALE SWEAT)
- 15X17" BRINE TANK (275LB SALT CAPACITY)
- BRINE WELL WITH CAPS
- #500 AIR CHECK ASSEMBLY
- OVERFLOW FITTING
- OWNERS MANUAL
- SHIPPING CARTON

268-440i/460i-1" CONTROL FEATURES

- CHOICE OF 6 OR 7 DAY CLOCK, OR METERED DEMAND
- 12VOLT TRANSFORMER PROVIDES SAFE INSTALLATION
- 5- CYCLE DOWNFLOW BRINING CONTROL VALVE
- 7 DAY VARIABLE RESERVE/CALENDAR OVERRIDE (460I ONLY)
- NON-CORROSIVE NORYL CONSTRUCTION
- AUTOTROL'S DESIGN MAKES DISASSEMBLY A SNAP
- CUSTOMIZE INSTALLATION CHOOSING FROM A WIDE RANGE OF OPTIONS (SEE PAGE 16)
- FLOW RATE IS UP TO 20GPM
- BACKWASH CAPACITY HANDLES TANKS UP TO 13" DIA.

For More Information On The Series 440i & 460i Control Valves
 Please Call 800.426.9375 Or Visit www.pentairwater.com

SEE PAGE 16 FOR ACCESSORIES, DESIGNER TANK JACKETS AND OPTIONS

ALL PRICES F.O.B. SHIPPING POINT - TERMS NET (THIRTY) 30 DAYS

TOLL FREE ORDERING 800.426.9375
 11470 Kreutzer Road - Huntley, Illinois 60142 - Office (847)669.1902 - Fax (847)669.1937

INTERNATIONAL WATERWORKS inc.
 E-Mail us @ iwaterworks@aol.com
 Please visit our web site @ www.iwaterworks.com
 PRICES SUBJECT TO CHANGE WITHOUT NOTICE

AUTOTROL L268 ASSEMBLED SOFTENERS

REVISED 01.01.2010

L268 RISER TWO TANK & CABINET SOFTENER SYSTEMS

| MODEL NUMBER | TANK SIZE | GRAINS CAPACITY | CUBIC FEET | BW Assy# | DLFC (Gpm) | INJECTOR COLOR | CLOCK LIST | METER LIST |
|---------------------------------|-----------|-----------------|------------|----------|------------|----------------|------------|------------|
| L268*R16 | 7x44" | 16,000 | .50cf | 7 | 1.3 | Peach-F | 618.62 | 788.84 |
| L268*R24 | 8x44" | 24,000 | .75cf | 8 | 1.7 | Tan-G | 640.32 | 810.53 |
| L268*R32 | 9x48" | 32,000 | 1.0cf | 9 | 2.2 | Lt.Purple-H | 683.74 | 853.96 |
| L268*R40 | 10x44" | 40,000 | 1.25cf | 10 | 2.7 | Lt.Blue-J | 713.84 | 884.05 |
| L268*R48 | 10x54" | 48,000 | 1.50cf | 10 | 2.7 | Lt.Blue-J | 749.65 | 919.87 |
| L268*R56 | 12x48" | 56,000 | 1.75cf | 12 | 3.9 | Pink-K | 814.68 | 984.89 |
| L268*R64 | 12x52" | 64,000 | 2.0cf | 12 | 3.9 | Pink-K | 849.22 | 1019.43 |
| L268*R80 | 13x54" | 80,000 | 2.50cf | 13 | 4.5 | Orange-L | 935.61 | 1105.82 |
| CABINET SOFTENER SYSTEMS | | | | | | | | |
| L268*R16C | 7x35" | 16,000 | .50cf | 7 | 1.3 | Peach-F | 641.29 | 811.50 |
| L268*R24C | 9x35" | 24,000 | .75cf | 9 | 2.2 | Lt.Purple-H | 678.11 | 848.32 |
| L268*R32C | 10x35" | 32,000 | 1.0cf | 10 | 2.7 | Lt.Blue-J | 707.29 | 877.50 |

L268 TURBULATOR TWO TANK & CABINET SOFTENER SYSTEMS

| MODEL NUMBER | TANK SIZE | GRAINS CAPACITY | CUBIC FEET | BW Assy# | DLFC (Gpm) | INJECTOR COLOR | CLOCK LIST | METER LIST |
|---------------------------------|-----------|-----------------|------------|----------|------------|----------------|------------|------------|
| L268*T16 | 7x35" | 16,000 | .50cf | 9 | 2.2 | Peach-F | 640.56 | 810.77 |
| L268*T24 | 7x44" | 24,000 | .75cf | 9 | 2.2 | Peach-F | 669.84 | 840.05 |
| L268*T32 | 8x44" | 32,000 | 1.0cf | 10 | 2.7 | Tan-G | 691.53 | 861.74 |
| L268*T40 | 9x48" | 40,000 | 1.25cf | 10 | 2.7 | Lt.Purple-H | 734.96 | 905.17 |
| L268*T48 | 10x44" | 48,000 | 1.50cf | 12 | 3.9 | Lt.Blue-J | 766.93 | 937.14 |
| L268*T56 | 10x47" | 56,000 | 1.75cf | 12 | 3.9 | Lt.Blue-J | 791.20 | 961.41 |
| L268*T64 | 10x54" | 64,000 | 2.0cf | 12 | 3.9 | Lt.Blue-J | 822.23 | 992.44 |
| L268*T80 | 12x48" | 80,000 | 2.50cf | 13 | 4.5 | Pink-K | 911.41 | 1081.62 |
| CABINET SOFTENER SYSTEMS | | | | | | | | |
| L268*T16C | 7x35" | 16,000 | .50cf | 9 | 2.2 | Peach-F | 671.14 | 841.35 |
| L268*T24C | 8x35" | 24,000 | .75cf | 10 | 2.7 | Tan-G | 696.29 | 866.50 |
| L268*T32C | 9x35" | 32,000 | 1.0cf | 10 | 2.7 | Lt.Purple-H | 728.87 | 899.08 |
| L268*T40C | 10X35" | 40,000 | 1.25cf | 12 | 3.9 | Lt.Blue-J | 758.05 | 928.26 |

* ADD THE LETTER "M" TO THE MODEL NUMBER HERE IF UNIT IS METERED

STANDARD FEATURES

- POLYGLASS WOUND PRESSURE VESSEL
- HIGH CAPACITY CATION RESIN
- 1.050" DISTRIBUTOR SYSTEM
- 3/4 COPPER TAIL KIT (MALE SWEAT)
- 15X17" BRINE TANK (275LB SALT CAPACITY)
- OVAL BRINE WELL WITH CAPS
- #500 AIR CHECK ASSEMBLY
- OVERFLOW FITTING
- OWNERS MANUAL
- SHIPPING CARTON

L268-740/760-1" CONTROL FEATURES

- SIMPLE ELECTRONIC 740 TIME CLOCK & 760 METER DEMAND
- 12VOLT TRANSFORMER PROVIDES SAFE INSTALLATION
- 28 DAY VARIABLE RESERVE (LOGIX 760 ONLY)
- HIGH EFFICIENCY REGENERATION SEQUENCE
- DOWNFLOW BRINING CONTROL VALVE
- NON-CORROSIVE NORYL CONSTRUCTION
- AUTOTROL'S DESIGN MAKES DISASSEMBLY A SNAP
- CUSTOMIZE INSTALLATION CHOOSING FROM A WIDE RANGE OF OPTIONS (SEE PAGE 16)
- FLOW RATE IS UP TO 20GPM
- BACKWASH CAPACITY HANDLES TANKS UP TO 13" DIA.

For More Information On The LOGIX 740 & 760 Control Valves
Please Call 800.426.9375 Or Visit www.pentairwater.com

SEE PAGE 16 FOR ACCESSORIES, DESIGNER TANK JACKETS AND OPTIONS

ALL PRICES F.O.B. SHIPPING POINT - TERMS NET (THIRTY) 30 DAYS

TOLL FREE ORDERING 800.426.9375

11470 Kreutzer Road - Huntley, Illinois 60142 - Office (847)669.1902 - Fax (847)669.1937

INTERNATIONAL WATERWORKS inc.
 E-Mail us @ iwaterworks@aol.com
 Please visit our web site @ www.iwaterworks.com
 PRICES SUBJECT TO CHANGE WITHOUT NOTICE

AUTOTROL LL268 ASSEMBLED SOFTENERS

REVISED 01.01.2010

LL268 RISER TWO TANK & CABINET SOFTENER SYSTEMS

| MODEL NUMBER | TANK SIZE | GRAINS CAPACITY | CUBIC FEET | BW Assy# | DLFC (Gpm) | INJECTOR COLOR | CLOCK LIST | METER LIST |
|---------------------------------|-----------|-----------------|------------|----------|------------|----------------|------------|------------|
| LL268*R16 | 7x44" | 16,000 | .50cf | 7 | 1.3 | Peach-F | 650.65 | 821.23 |
| LL268*R24 | 8x44" | 24,000 | .75cf | 8 | 1.7 | Tan-G | 672.35 | 842.93 |
| LL268*R32 | 9x48" | 32,000 | 1.0cf | 9 | 2.2 | Lt.Purple-H | 715.77 | 886.35 |
| LL268*R40 | 10x44" | 40,000 | 1.25cf | 10 | 2.7 | Lt.Blue-J | 745.87 | 916.44 |
| LL268*R48 | 10x54" | 48,000 | 1.50cf | 10 | 2.7 | Lt.Blue-J | 781.68 | 952.26 |
| LL268*R56 | 12x48" | 56,000 | 1.75cf | 12 | 3.9 | Pink-K | 846.71 | 1017.28 |
| LL268*R64 | 12x52" | 64,000 | 2.0cf | 12 | 3.9 | Pink-K | 881.25 | 1051.83 |
| LL268*R80 | 13x54" | 80,000 | 2.50cf | 13 | 4.5 | Orange-L | 967.64 | 1138.21 |
| CABINET SOFTENER SYSTEMS | | | | | | | | |
| LL268*R16C | 7x35" | 16,000 | .50cf | 7 | 1.3 | Peach-F | 673.32 | 843.90 |
| LL268*R24C | 9x35" | 24,000 | .75cf | 9 | 2.2 | Lt.Purple-H | 710.14 | 880.71 |
| LL268*R32C | 10x35" | 32,000 | 1.0cf | 10 | 2.7 | Lt.Blue-J | 739.32 | 909.90 |

LL268 TURBULATOR TWO TANK & CABINET SOFTENER SYSTEMS

| MODEL NUMBER | TANK SIZE | GRAINS CAPACITY | CUBIC FEET | BW Assy# | DLFC (Gpm) | INJECTOR COLOR | CLOCK LIST | METER LIST |
|---------------------------------|-----------|-----------------|------------|----------|------------|----------------|------------|------------|
| LL268*T16 | 7x35" | 16,000 | .50cf | 9 | 2.2 | Peach-F | 672.59 | 843.17 |
| LL268*T24 | 7x44" | 24,000 | .75cf | 9 | 2.2 | Peach-F | 701.87 | 872.44 |
| LL268*T32 | 8x44" | 32,000 | 1.0cf | 10 | 2.7 | Tan-G | 723.56 | 894.14 |
| LL268*T40 | 9x48" | 40,000 | 1.25cf | 10 | 2.7 | Lt.Purple-H | 766.99 | 937.56 |
| LL268*T48 | 10x44" | 48,000 | 1.50cf | 12 | 3.9 | Lt.Blue-J | 798.96 | 969.53 |
| LL268*T56 | 10x47" | 56,000 | 1.75cf | 12 | 3.9 | Lt.Blue-J | 823.23 | 993.80 |
| LL268*T64 | 10x54" | 64,000 | 2.0cf | 12 | 3.9 | Lt.Blue-J | 854.26 | 1024.84 |
| LL268*T80 | 12x48" | 80,000 | 2.50cf | 13 | 4.5 | Pink-K | 943.44 | 1114.02 |
| CABINET SOFTENER SYSTEMS | | | | | | | | |
| LL268*T16C | 7x35" | 16,000 | .50cf | 9 | 2.2 | Peach-F | 703.17 | 873.74 |
| LL268*T24C | 8x35" | 24,000 | .75cf | 10 | 2.7 | Tan-G | 728.32 | 898.90 |
| LL268*T32C | 9x35" | 32,000 | 1.0cf | 10 | 2.7 | Lt.Purple-H | 761.35 | 931.93 |
| LL268*T40C | 10X35" | 40,000 | 1.25cf | 12 | 3.9 | Lt.Blue-J | 790.53 | 961.11 |

* ADD THE LETTER "M" TO THE MODEL NUMBER HERE IF UNIT IS METERED

STANDARD FEATURES

- POLYGLASS WOUND PRESSURE VESSEL
- HIGH CAPACITY CATION RESIN
- 1.050" DISTRIBUTOR SYSTEM
- 3/4 COPPER TAIL KIT (MALE SWEAT)
- 15X17" BRINE TANK (275LB SALT CAPACITY)
- OVAL BRINE WELL WITH CAPS
- #500 AIR CHECK ASSEMBLY
- OVERFLOW FITTING
- OWNERS MANUAL
- SHIPPING CARTON

LL268-742/762-1" CONTROL FEATURES

- SIMPLE ELECTRONIC 742 TIME CLOCK & 762 METER DEMAND
- FULLY PROGRAMMABLE CYCLE TIMES
- 12VOLT TRANSFORMER PROVIDES SAFE INSTALLATION
- 28 DAY VARIABLE RESERVE (LOGIX 762 ONLY)
- DOWNFLOW BRINING CONTROL VALVE
- NON-CORROSIVE NORYL CONSTRUCTION
- AUTOTROL'S DESIGN MAKES DISASSEMBLY A SNAP
- CUSTOMIZE INSTALLATION CHOOSING FROM A WIDE RANGE OF OPTIONS (SEE PAGE 16)
- FLOW RATE IS UP TO 20GPM
- BACKWASH CAPACITY HANDLES TANKS UP TO 13" DIA.

For More Information On The LOGIX 742 & 762 Control Valves
Please Call 800.426.9375 Or Visit www.pentairwater.com

SEE PAGE 16 FOR ACCESSORIES, DESIGNER TANK JACKETS AND OPTIONS

ALL PRICES F.O.B. SHIPPING POINT - TERMS NET (THIRTY) 30 DAYS

TOLL FREE ORDERING 800.426.9375

11470 Kreutzer Road - Huntley, Illinois 60142 - Office (847)669.1902 - Fax (847)669.1937

INTERNATIONAL WATERWORKS inc.
 E-Mail us @ iwaterworks@aol.com
 Please visit our web site @ www.iwaterworks.com
 PRICES SUBJECT TO CHANGE WITHOUT NOTICE

ACCESSORIES

| PART # | DESCRIPTION | LIST |
|----------|------------------------------------|-------|
| 1040547 | 90° Plastic Coupling (Space Saver) | 17.76 |
| 05008102 | 1.050" Upper Distributor Screen | 2.69 |

255 OPTIONS ADDERS

| | | |
|------------|---------------------------------|--------|
| 1040539 | Plastic Yoke 3/4" fpt | -13.03 |
| 1040538 | Brass Yoke 1" fpt | 13.27 |
| 1040769-75 | 256 Bypass w/3/4" Copper Tails | 31.76 |
| 1040769-1 | 256 Bypass w/1" Copper Tails | 33.76 |
| 1040769-12 | 256 Bypass w/1.25" Copper Tails | 35.70 |
| 1047pvc-75 | 256 Bypass w/3/4" PVC Tails | 35.88 |
| 1047pvc-1 | 256 Bypass w/1 PVC Tails | 35.88 |
| 1033025 | Extra Salt & Long Rinse Cam-255 | 8.15 |
| 1033026 | Long Rinse Cam-255 | 2.15 |

263/268 OPTIONS ADDERS

| | | |
|------------|----------------------------------|-------|
| 1040930 | 1265 Bypass Only | 53.48 |
| 1001670 | 1" Copper Tail Kit | 2.00 |
| 1041210 | 1.25" Copper Tail Kit | 3.94 |
| 1001613 | 3/4" PVC Tail Kit | 4.12 |
| 1001614 | 1" PVC Tail Kit | 4.12 |
| 1040930-1 | 1265 Bypass w/1" Copper Tails | 55.48 |
| 1040930-12 | 1265 Bypass w/1.25" Copper Tails | 57.42 |
| 1049-75pvc | 1265 Bypass w/3/4" PVC Tails | 57.61 |
| 1049-1pvc | 1265 Bypass w/1" PVC Tails | 57.61 |
| 0000000 | All Performa Cams Options | N/C |

DESIGNER JACKETS

| | | |
|-------|-------------------------------|-------|
| D07__ | 7"Almond, Black, Blue, White | 23.64 |
| D08__ | 8"Almond, Black, Blue, White | 23.99 |
| D09__ | 9"Almond, Black, Blue, White | 26.27 |
| D10__ | 10"Almond, Black, Blue, White | 31.33 |
| D12__ | 12"Almond Only | 56.20 |
| D13__ | 13"Almond Only | 64.90 |

__Please Specify Color: Almond (A), Black (BL), Blue (B), White (W)
 Chrome Jacket Are Also Available Please Call For Pricing

GRAVEL UNDER BEDDING OPTIONS

NOTE: FOR RISER MODELS ONLY To Improve Flow Rates

| | | | |
|------|----------|--|------|
| 6LB | 7" Tank | WARNING: DO NOT INSTALL UNDER BEDDING TO UNITS THAT HAVE TURBULATORS !! | 1.91 |
| 9LB | 8" Tank | | 2.39 |
| 12LB | 9" Tank | | 2.86 |
| 15LB | 10" Tank | IT WILL CAUSE THE TURBULATOR TO MALFUNCTION | 3.58 |

NOTE: Assembled Softeners using 12" Tanks & Above Include Gravel

BRINE TANK OPTIONS

| PART # | DESCRIPTION | LIST |
|--------|--|--------|
| B1138_ | 11x11x38" Brine Tank (156lbs. Salt Cap.) | - 5.88 |
| B1434_ | 14x14x34" Brine Tank (225lbs. Salt Cap.) | - 2.27 |
| B1833_ | 18x33" Brine Tank (375lbs. Salt Cap.) | 1.88 |
| B1840_ | 18x40" Brine Tank (450lbs. Salt Cap.) | 7.73 |

__Please Specify Color: Almond (A), Black (BL), Blue (B), White (W)

BRINE TANK INJECTION MOLDED LIDS

NOTE: Matches Tank Jacket Cap (Black Textured)

| | | |
|-------|---------------------------|-------|
| T11 | 11" Black Textured Lid | 12.00 |
| T14 | 14" Black Textured Lid | 2.67 |
| T1517 | 15x17" Black Textured Lid | 6.12 |
| T18 | 18" Black Textured Lid | 10.27 |

BRINE WELL OPTIONS

| | | |
|------|-----------------------------------|------|
| B332 | 3.5x32" Slotted Brine Well & Caps | .45 |
| B336 | 3.5x36" Slotted Brine Well & Caps | 1.12 |
| B430 | 4x30" Slotted Brine Well & Caps | 1.24 |
| B432 | 4x32" Slotted Brine Well & Caps | 1.61 |
| B436 | 4x36" Slotted Brine Well & Caps | 2.52 |

2300 & 2310 SAFETY SHUT OFFs

NOTE: Safety Shut Offs Help Prevent Brine Tank Overflow

| | | |
|-----|---------------------------------------|-------|
| 230 | 2300 Brass Safety Shut Off With Float | 40.52 |
| 231 | 2310 Plastic Safety Shut Off With | 19.88 |

BRINE TANK GRID OPTIONS

NOTE: Salt Grids Help Prevent The Salt From Bridging

| | | |
|------|----------------------------|-------|
| 11PL | 11x11" Plastic Salt Grid | 11.79 |
| 14PL | 14x14" Plastic Salt Grid | 11.79 |
| 15PL | 15x17" Plastic Salt Grid | 11.79 |
| 18PL | 18" Plastic Salt Grid | 11.79 |
| CMPL | Cabinet Model Plastic Grid | 11.79 |

AUTOTROL (PENTAIR) LIMITED WARRANTY

Warrants that all products it sells will be free from defects in materials and workmanship for a period of Sixty (60) months from date of shipment. Copies Of Warranty Are Available

ALL PRICES F.O.B. SHIPPING POINT - TERMS NET (THIRTY) 30 DAYS

TOLL FREE ORDERING 800.426.9375
 11470 Kreutzer Road - Huntley, Illinois 60142 - Office (847)669.1902 - Fax (847)669.1937